

G 型

| サイズ | 転造能力 最小～最大 | D | D1 | D2 | D3 | D4(シャンク) ミリ インチ | | D5 | L | L1 | L2 | L3 | L4 | a | | 重量 Kg |
|--------|---------------|------|------|------|-----|-------------------------------------|---------|-----|-------|----|------|-------|-----|-----|-----|----------|
| 0 | M1.4 ~ 5.5 | 50 | 54.5 | 11.5 | M6 | 20 | 3/4 | 6.5 | 89 | 50 | 39 | 98 | 5 | 2 | 50° | 0.55 |
| 001 | M2.6 ~ 4 | 40 | - | 7 | M6 | 16,20 | 3/4,5/8 | 7.5 | 65.4 | 25 | 40.4 | 72.9 | 2.5 | 1.5 | 32° | 0.3 |
| 01 | M3.5 ~ 6 | 40 | - | 12 | M6 | 16,20 | 3/4,5/8 | 7.5 | 70.3 | 25 | 45.3 | 77.8 | 4.5 | 1.5 | 32° | 0.34 |
| 1 | M6 ~ 11 | 64 | 69.5 | 17 | M10 | 20 | 3/4 | 11 | 110 | 60 | 50 | 124 | 6 | 2 | 60° | 0.85 |
| 12 | M6 ~ 12 | 64 | 69 | 20 | M10 | 20 | 3/4 | 11 | 111.5 | 60 | 51.5 | 125.5 | 6 | 2 | 60° | 0.85 |
| 1223 | M5 ~ 8 | 56 | 58 | 16 | M8 | 16,20 | 3/4 | 8.2 | 91 | 40 | 51 | 104 | 5 | 2 | 50° | 0.65 |
| 2 | M8 ~ 16 | 88.5 | 92.5 | 22 | M12 | 25 | 1 | 17 | 145 | 76 | 69 | 163 | 8 | 3 | 60° | 2 |
| 23 | M8 ~ 22 | 88 | 92 | 28 | M12 | 25 | 1 | 17 | 148 | 78 | 70 | 166 | 7.5 | 3 | 60° | 2 |
| 233400 | M16 ~ 36 | 96 | 115 | 39 | M12 | 25 | 1 | 14 | 142.5 | 60 | 82.5 | 160.5 | 8 | 3 | 30° | 2.9 |
| 3 | M12 ~ 22 | 117 | 131 | 35 | M16 | 30 | 1 1/4 | 22 | 173.5 | 90 | 83.5 | 197 | 8 | 4 | 60° | 4 |
| 34 | M12 ~ 30 | 117 | 128 | 44 | M16 | 30 | 1 1/4 | 22 | 175 | 87 | 88 | 198 | 8 | 4 | 60° | 4 |