

F 型

サイズ	転造能力 最小～最大	D	D1	D2	D3	D4(シャンク) ミリ インチ		D5	L	L1	L2	L3	L4	a		重量 kg
0	M1.4～5.5	50	54.5	11.5	M6	20	3/4	6.5	89	50	39	98	5	2	50°	0.55
001	M2.6～4	40	-	7	M6	16,20	3/4,5/8	7.5	65	25	40	73	2.5	1.5	32°	0.3
01	M3.5～6	40	-	12	M6	16,20	3/4,5/8	7.5	68	24.5	43.5	77.5	4.5	1.5	32°	0.34
1	M6～11	64	69.5	17	M10	20	3/4	11	110	60	50	124	6	2	60°	0.85
12	M6～12	64	69	20	M10	20	3/4	11	112	60	51.5	126	6	2	60°	0.85
1223	M5～8	56	58	16	M8	16,20	3/4	8.2	91	40	51	104	5	2	50°	0.65
2	M8～16	88.5	92.5	22	M12	25	1	17	145	76	69	163	8	3	60°	2
23	M8～22	88	92	28	M12	25	1	17	148	78	70	166	7.5	3	60°	2
233400	M16～36	96	115	39	M12	25	1	14	143	60	82.5	161	8	3	30°	2.9
3	M12～22	117	131	35	M16	30	1 1/4	22	174	90	83.5	197	8	4	60°	4
34	M12～30	117	128	44	M16	30	1 1/4	22	175	87	88	198	8	4	60°	4